



COMMERCIAL

FlexLok

Carpet Tiles

Technical Specifications

Spécifications techniques - Technische specificaties - Technische Spezifikationen

| | |
|---|--------------------------------|
| Adhesive carrier Support adhésif - zelfklevende drager - Klebender Träger | Selfwound, Linerfree system |
| Adhesive system Système adhésif - Lijmsysteem - Klebesystem | Acrylic dispersion |
| Liner Doublure - Voering - Futter | Transparent polyester film |
| Thickness (without liner) Épaisseur (sans doublure) - Dikte (zonder voering) - Dicke (ohne Futter) | 0,215 mm |
| Peel Adhesion Adhérence - Hechting - Haftfestigkeit | EcoFlex™ Statera = 320 N/Meter |
| Peel Adhesion Adhérence - Hechting - Haftfestigkeit | EcoFlex™ Echo = 420 N/Meter |
| Recommended processing temperature Température de traitement recommandée - Aanbevolen verwerkingstemperatuur - Empfohlene Verarbeitungstemperatur | +10 °C tot +30°C |
| Temperature resistance Résistance à la température - Temperatuurbestendigheid - Temperaturbeständigkeit | -40 °C tot +140°C |
| Aging resistance Comportement au vieillissement - Verouderingsbestendigheid - Alterungsbeständigkeit | Very high |
| Plasticizer resistance Résistance au plastifiant - Weekmaker weerstand - Weichmacherbeständigkeit | Very high |
| Tack Force adhésive - Kleefsterkte - Haftfestigkeit | High |
| Number of adhesive tabs Nombre d'autocollants - Aantal stickers - Anzahl klebeecken | 200/box |

We reserve all rights for technical improvements.