



COMMERCIAL

SPECIFICATION TEXT CARPET TILES

BASALT on EcoFlex™ Echo

Installation method: fully fixed

TUFTED CARPET TILES

Manufacturer: IVC Commercial

Product name: Basalt

Colour: According to the manufacturer's colour chart

Manufacturing method: Tufted 1/12" gauge loop

Size: 50x50 cm

Total weight: Ca. 4700 g/m²

Pile weight: Ca. 600 g/m²

Surface pile weight: Ca. 390 g/m²

Total thickness: Ca. 8,4 mm

Number of tufts: Ca. 219.300/m²

Pile fibre composition: 100% solution dyed nylon

Secondary backing: EcoFlex™ Echo – 94% recycled PES felt

Total recycled content: 52%

Wear classification (EN 1307): 33/LC1

Dimensional stability (EN 986): ≤ 0,2 %

Impact sound reduction (ISO 10140-3): ΔLw: 32dB

Sound absorption (ISO 354): 0,25 aw

Fire classification (EN 13501-1): Blf-s1

Colour fastness (ISO 105-B02): ≥ 7

Additional properties (EN 1307):

- Slip resistance: DS
- Castor chair suitability (EN 985): A : intensive use
- Permanent antistatic (ISO 6356): ≤ 2 kV

Warranty: 15 years

This product meets the GUT criteria. This criteria includes limit values for VOCs, odours and chemicals.

GUT Prodis number: 65EB708B

The details of this text serve as an informative guide to tenders. Technical data may change slightly, current data can be found at: www.ivc-commercial.com

Version: July 2021